

LAP20 Rec'd CRYPTO 21 APR 2006

[001]

[002]

[003]

[004]

[005]

[006]

[007]

[008]

axially displaceable in the housing, running over bearing bolts, whereby the axial displacement of the external part is carried over the roller bearings.

[009] The sliding collar displacement takes place by means of a switching device, which is actuated by a solenoid or by a motorized switching unit whose armature is connected with the sliding collar.

[010] This kind of planetary transmission has multiple rotating elements and, consequently, many bearings which are lubricated with the appropriate oil. Most of the traditional planetary transmissions for machine tools use splash lubrication, which has the disadvantage that it may be tainted with high mix losses and that the maximum possible rotational speed of the internal gear is limited by the internal gear bearings as they get warm, as the absorbed heating cannot be released. It is possible to cool the splash lubrication oil with circulatory lubrication, without avoiding the mix losses.

[011] Further planetary transmissions are built with circulatory lubrication and oil cooling. High mix losses are shown also in these cases, on which the target maximum rotational speed of the interior gear is only possible conditionally. Under very high rotational speeds, the oil from the central part will be shot by the centrifugal force towards the housing, leaving the center of the transmission with a low oil level during the operation, generating frictional corrosion.

[012] Operation of a planetary transmission with oil spray lubrication has also been tried. This is however not applicable for planetary transmissions, as the oil spray cannot reach the center of the transmission because of the strong ventilation effect caused by the high rotational speed of the interior gear, which means that the sun gear is not lubricated. Therefore the axial bearings will be insufficiently lubricated and frictional corrosion may even be generated.

[013] SUMMARY OF THE INVENTION

[014] The purpose of the present invention is to create a planetary transmission

with a lubrication circuit that is reliable under the high rotational speed of the interior gear and at the same time under low temperatures, so that no more frictional corrosion is generated.

[015] ~~—— The solution of this task follows from a planetary transmission of the type indicated, with the features mentioned in part 1 of the patent claims; some beneficial applications are described in the subsequent patent claims.~~

[016] The invention proceeds from a planetary transmission, in particular for machine tools, that has a drive shaft connected to a sun gear; an output shaft that is connected to a planetary carrier and that is mounted over the transmission housing with a first external bearing and with a second internal bearing, where both bearings are separated from each other by means of a piston ring; an axial bearing; an interior gear which is located over the interior gear bearing in the transmission housing; an axially displaceable sliding collar which is mounted over sliding collar bearings; and a transmission lubrication circuit with an oil pump.

[017] According to the invention, it is planned that the oil pump be located outside the transmission, that the housing has an oil intake, that this oil intake is connected to an oil line with the first external bearing of the output shaft, that the bushings have a small borehole for connecting the piston ring, that the first external bearing is connected to an oil supply circuit with the axial bearing, that the axial bearing is connected over a cavity with the interior gear bearing, where the cavity is encapsulated through a wall section for the oil discharge hole in the transmission housing, and that the oil discharge is connected to the oil pump by an oil line.

[018] With the invention based oil circuit application, it will be possible to handle higher rotational speeds of the interior gear based on lower temperatures, and no more frictional corrosion will be produced. It may be further possible to achieve a dry lubrication system, which means that no oil level will be necessary in the planetary transmission, by which also no mix losses and no temperature increase will occur, in comparison with the traditional planetary transmissions

that show different oil levels that depend on the rotation direction and that have detrimental effects on the oil temperature.

[019] The invention is explained in further detail in the only Fig., in which a section of a two-stage planetary transmission is shown, in particular for a machine tool, on which the proposed lubrication circuit can be seen.

[020] BRIEF DESCRIPTION OF THE DRAWINGS

[021] Two-stage planetary transmissions for machine tools are well known by specialists, therefore only the description required for understanding the parts of the proposed invention follows.

[022] DETAILED DESCRIPTION OF THE INVENTION

[023] The drive shaft of the transmission is identified with number 1. The sun gear to which it is connected is identified with number 2, while the output shaft is identified with number 3 and the planetary carrier to which they are connected with number 4. The oil intake is identified with number 13, the application example close to the switchgear is identified with number 19, which is intended for the sliding collar 11 in the bearings or in the transmission housing. This oil intake is connected with an oil pump (that is not shown) outside of the transmission, and with an oil line 16, which is built into the wall of the transmission housing with the first external bearing 5 of the drive shaft 3. The first external bearing 5 is sealed off from the second internal bearing 6 by a piston ring 8, whereby this piston ring 8 is provided with an opening. This opening can either be the small borehole 15 of the piston ring that penetrates the internal or external bushing parallel to the drive shaft axle, or a narrow gap between piston ring 8 and the external bushing, so that a small oil quantity is applied to the second internal bearing 6.

[024] The first external bearing 5 is connected with the axial bearing 9 over two parallel oil lines 16', 16" in the longitudinal axle of the output shaft, which in order to prevent unbalancing are placed over the longitudinal axle symmetrical levels

of the output shaft. Either a single oil line or more than two oil lines can be applied.

[025] Both of these oil lines 16' and 16" remain perpendicular to the output shaft over the longitudinal axle penetrating borehole 20 connection. Oil from the first external bearing 6 to the axial bearing 9 flows through this oil circuit.

[026] The oil flows to the output shaft center, where it arrives after flooding axial bearing 9 due to the rotational force in the direction of the housing inner wall. A cavity 17 runs through the closed bearing housing wall section 18, through which oil will flow to interior gear bearing 11, which will then be optimally lubricated and cooled, allowing the rotational speed to be increased. In the traditional planetary transmissions, the maximum rotational speed of the transmission is limited by the top rotational speed of the interior gear.

[027] The closed bearing housing on wall section 18 is encapsulated due to the rapidly turning interior gear 11, whereby the interior gear oil adulteration is prevented or at least significantly reduced, and a rotation direction depending oil level is also avoided.

[028] The interior gear bearing 11 is not connected with the sliding collar bearing 12 of the sliding collar 26, as this sliding collar bearing, which due to its small overall size is not critical for the rotational speed and in addition must not absorb any axial and/or radial forces, it can be lubricated with an oil spray.

[029] Provided that the planetary transmission has an adapter plate 21 between the drive shaft and the transmission, it will then have its own oil intake 23, on which an oil line 22 is attached for lubricating the associated bearing 24. This oil line 22 is provided with a discharge borehole 25, so that in case a high oil quantity circulates through it, there is also high oil pressure in line 22.

[030] In one (not shown) application example, instead of the oil intake 13 close to switchgear 19 there is a centered axial borehole in drive shaft 3, so that oil can flow through this centered borehole to oil lines 16', 16" and 20. The oil intake 13 may also serve for feeding.

[031] It should be stressed that it is also possible to deploy an oil circuit in the

opposite direction, which means that the above-described oil discharge 14 can be the oil intake, and the above described oil intake 13 can become the oil discharge.

[032] The continuous flow over the planetary transmission provides excellent lubrication, at the same time excellent oil cooling, and prevents the formation of frictional corrosion.

[033] The dry lubrication system according to the invention eliminates the need for an oil level together with adulteration and the until now unavoidable temperature increase. The selective lubrication of the individual machine components leads at the same time to a significant rotational speed increase of the internal gear by reducing the frictional corrosion. The encapsulation through wall section 18 contributes significantly to these benefits.

[034] Reference signs

1	Drive shaft
2	Sun gear
3	Output shaft
4	Planetary carrier
5	External gear
6	Interior gear
7	Housing
8	Piston ring
9	Axial bearing
10	Interior gear
11	Interior gear bearing
12	Sliding collar bearing
13	Oil intake
13'	Oil intake
14	Oil discharge
15	Borehole
16	Oil line
16'	Oil line
16"	Oil line
17	Cavity
18	Wall section
19	Switchgear
20	Oil line
21	Adapter plate
22	Oil line
23	Oil intake
24	Bearing
25	Discharge borehole
26	Sliding collar